AMENDMENT OF SOLICITAT	TION/MODIFICAT	TION OF CONTRACT	1. CONTR	ACT ID CODE	PAGE C	F PAGES
					1	3
2. AMENDMENT/MODIFICATION NO.	3. EFFECTIVE DATE	4. REQUISITION/PURCHASE REQ. NO. 5. PROJE			ECT NO.(If applicable)	
0001	20-Apr-2000			S.Enclade 50	04-862-1514	1
	DE DACW29	7. ADMINISTERED BY (If oth	er than item (6) CODE		
U.S. ARMY CORPS OF ENGINEERS, NEW ORLE ATTN: CEMVN-CT, ROOM 172 7400 LEAKI		See Item 6				
NEW ORLEANS, LA 70118						
8. NAME AND ADDRESS OF CONTRACTOR (N	Io., Street, County, State an	d Zip Code)	9A. AMEN DACW29-	DMENT OF S	OLICITAT	ION NO.
		>	9B. DATE	D (SEE ITEM	11)	
			03-Apr-20 10A. MOD	. OF CONTRA	CT/ORDER	NO.
CODE			10B. DAT	ED (SEE ITEN	M 13)	
CODE	FACILITY CODE	TO AMENDMENTS OF SOLICI	TATIONG			
			1			
The above numbered solicitation is amended as set forth in			is extended,	X is not ex	tended.	
Offers must acknowledge receipt of this amendment prior (a) By completing Items 8 and 15, and returning 1	=		-			
or (c) By separate letter or telegram which includes a refer						
RECEIVED AT THE PLACE DESIGNATED FOR THE						
REJECTION OF YOUR OFFER. If by virtue of this amen provided each telegram or letter makes reference to the so				or letter,		
12. ACCOUNTING AND APPROPRIATION DATA	A (If required)					
		DIFICATIONS OF CONTRACTS/C DER NO. AS DESCRIBED IN ITEM				
A.THIS CHANGE ORDER IS ISSUED PURSUA CONTRACT ORDER NO. IN ITEM 10A.				RE MADE IN T	ГНЕ	
B.THE ABOVE NUMBERED CONTRACT/ORD office, appropriation date, etc.) SET FORTH				uch as changes	in paying	
C.THIS SUPPLEMENTAL AGREEMENT IS E						
D.OTHER (Specify type of modification and aut	hority)					
E. IMPORTANT: Contractor is not,	is required to sign this d	locument and return c	opies to the is	suing office.		
14. DESCRIPTION OF AMENDMENT/MODIFICATION where feasible.)	ATION (Organized by UCI	F section headings, including solicit	ation/contrac	t subject matter	•	
The above numbered solicitation for SELA, Keyh hereby amended as follows:	ole Canal Phase II, Canal	Paving, Westbank Expressway to	WPA Canal,	Jefferson Par	ish, LA, is	
	BID OPENING DATE					
BID OPENING DATE & TIME OF 3 MAY 2000, 2:00		ACE OF BID OPENING. REMAINS L	INCHANGED.			
,,,,,		,				
Except as provided herein, all terms and conditions of the docur		= = =				
15A. NAME AND TITLE OF SIGNER (Type or page 15)		6A. NAME AND TITLE OF CONT			e or print)	
15B. CONTRACTOR/OFFEROR		SAROL J. SCHWARTZ / CONTRACT SB. UNITED STATES OF AMERIC			6C. DATE S	SIGNED
133. CONTRACTOR OF LINOR			J. 1.		UC. DAIL	,1011111
(Signature of person authorized to sign)	<u>B</u>	(Signature of Contracting Office	er)		17-Apr-200)0
(6 mm r		,	,			

EXCEPTION TO SF 30 APPROVED BY OIRM 11-84

30-105-04

STANDARD FORM 30 (Rev. 10-83) Prescribed by GSA FAR (48 CFR) 53.243

SPECIFICATIONS:

Section 00700 – CONTRACT CLAUSES

Page 60, 52.232-5001 CONTINUING CONTRACTS (MAR 1995) EFARS, paragraph (b). Delete "\$800,000.00" and substitute "\$600,000.00"

Section 01100 - GENERAL PROVISIONS

Page 01100-18, paragraph 17. b. Staged Excavation. Delete the text of the 1st paragraph and substitute the following text:

"Excavation of the bottom of the canal shall be staged to prevent shallow failures. The excavation to place the 18 inch thick bedding material beneath the canal bottom shall be limited to that which can be excavated and backfilled with bedding at the end of each work day. The Contractor shall not excavate more than what can backfilled in one working day. The Contractor shall not store any material within ten (10) feet of the top of the canal bank."

Section 02318 - EXCAVATION

Page 02318-3, paragraph 3.1.1 General. Delete the text of the 2nd paragraph and substitute the following text:

"Excavation of the bottom of the canal shall be staged to prevent shallow failures. The excavation to place the 18 inch thick bedding material beneath the canal bottom shall be limited to that which can be excavated and backfilled with bedding at the end of each work day. The Contractor shall not excavate more than what can be backfilled in one working day. The Contractor shall not store any material within ten (10) feet of the top of the canal bank. The Contractor, at his option may use a temporary retaining structure in accordance with 01100 - 17. b."

Section 02411 - SHEET PILING

Page 02411-3, paragraph 1.6. Insert the following reference standards:

"D 638 (1994b) Tensile Properties of Plastics
D 1784 (1992) Rigid Poly (Vinyl Chloride) (PVC) Compounds and

Chlorinated Poly (Vinyl Chloride) (PVC Compounds)"

Page 02411-7, paragraph 2.3. In the first sentence, delete ASTM D 4216, and substitute "ASTM D 1784". In the dimensions listed, for "Section Modulus", delete, "10.5 cu. in./ft." and substitute, "13 cu. In./ft."

Page 02411-6, paragraph 2.1 STEEL SHEET PILING. Delete the "PROPERTIES OF SECTIONS" table and insert the following revised table:

PROPERTIES OF SECTIONS

Type of section	Nominal web thickness (inches)	Section modulus (in ³ /ft of wall)	Moment of inertia (in ⁴)	Nominal section depth (inches)	Minimum interlock strength (lbs/lin in)	Theoretical driving width (inches)
PZ 27	0.335	30.2	276.3	12	N/A	18

Page 02411-6, paragraph 2.1.3. Delete the table, and substitute the following table:

Section designated on the	Substitute section			
Contract drawings	Minimum section modulus (in. ³ /ft. of wall)	nominal depth (inches)		
SZ 24	29.0	12.0		

DRAWINGS.

Delete drawings 2, 4, and 9 of 25, file number H-8-45201, and substitute the attached revised drawings 2, 4, and 9 of 25, dated 4/00.